## IN THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

## **LISTING OF CLAIMS:**

1. (Currently Amended) A verification system for a packet call processing operation of a mobile telephone, the verification system comprising:

a terminal for transmitting a packet call <u>control signal</u> request message to the mobile telephone to establish a packet call for communication of packets with the mobile telephone, generating an <u>internet</u> protocol packet after establishment of the packet call, transmitting <u>the internet protocol packet</u> it to the mobile telephone, and determining data processing characteristics of the mobile telephone based on a response packet received from the mobile telephone; and

a packet service simulator for receiving a response control message to the packet call control signal request message from the mobile telephone to verify the control message packet call processing operation between the terminal and the mobile telephone, and transmitting the internet Internet protocol packet received from the mobile telephone to an external network and transmitting a corresponding response packet received from the external network to the mobile telephone, thereby enabling the mobile telephone to transmit the corresponding response packet to the terminal.

- 2. (Currently Amended) The verification system as claimed in claim 1, wherein an <a href="internet">internet</a> protocol address is individually assigned to the terminal, the mobile telephone, and the packet service simulator.
- 3. (Original) The verification system as claimed in claim 1, wherein the mobile telephone is linked to the packet service simulator via a local area network (LAN), the packet

Application No. <u>10/022,729</u>

Amendment dated January 30, 2005

Page 4

service simulator being linked to the external network.

4. (Currently Amended) The verification system as claimed in claim 1, wherein the packet service simulator analyzes the <u>packet call response</u> control <u>signal message</u> received from the mobile telephone, generates <u>the corresponding</u> a response packet when the response control message is successfully processed, and transmits it to the mobile telephone to establish the packet call.

5. (Currently Amended) The verification system as claimed in claim 2, wherein the packet service simulator comprises:

a packet transmitter for transmitting data having an <u>internet</u> <u>Internet</u> protocol address of the terminal to the external network in an Ethernet packet format; and

a packet receiver for receiving a <u>the corresponding response</u> packet destined for the <u>internet Internet</u> protocol address of the terminal from the external network and transmitting <u>the corresponding response packet</u> it to the mobile telephone, thereby enabling the mobile telephone to transfer the <u>corresponding response</u> packet to the terminal.

- 6. (Currently Amended) The verification system as claimed in claim 2, wherein the packet service simulator receives the <u>corresponding response</u> packet destined for the <u>internet Internet</u> protocol access of the terminal in response to an address resolution protocol (ARP) request for the <u>internet Internet</u> protocol address of the terminal, sent from the external access network, using its physical address.
- 7. (Currently Amended) The verification system as claimed in claim 1, wherein the terminal executes a network application including Telnet, file transfer protocol (FTP), or the Web to generate an internet Internet protocol packet and transmit the internet protocol

<u>packet</u> it to the mobile telephone, and receives a response packet to the <u>internet</u> Internet protocol packet from the mobile telephone to verify network data processing operations of the mobile telephone.

- 8. (Original) The verification system as claimed in claim 1, wherein the terminal is linked to the mobile telephone via a universal serial bus (USB).
- 9. (Original) The verification system as claimed in claim 1, wherein the terminal communicates packets with the mobile telephone according to a point-to-point protocol (PPP).
- 10. (Original) The verification system as claimed in claim 1, wherein a physical layer of the mobile telephone comprises an Ethernet, and a media control layer of the mobile telephone is modified into a module for supporting the Ethernet.
- 11. (Currently Amended) A verification method for a packet call processing operation of a mobile telephone, in which the mobile telephone is connected to a terminal and a packet service simulator that is linked to an external network, the verification method comprising:

upon the mobile telephone receiving a packet call <u>control signal</u> request for verification of a packet data service from the terminal and transmitting a <u>corresponding</u> <u>packet</u> call request control <u>signal</u> message, the packet service simulator analyzing the <u>packet</u> call request control <u>signal</u> message received from the mobile telephone and verifying <u>control signal</u> the packet call processing <u>operation</u> between the mobile telephone and the terminal;

upon successful control signal processing, the packet service simulator generating a packet corresponding to a response signal to the packet call request control message and

transmitting it to the mobile telephone, thereby establishing a packet call to the mobile

telephone;

the terminal executing a network application, generating an internet Internet protocol

packet and transmitting it the intent protocol packet to the mobile telephone;

upon receiving the internet Internet protocol packet having an internet Internet

protocol address of the terminal from the mobile telephone, the packet service simulator

transmitting the internet Internet protocol packet to the an external network;

the packet service simulator receiving a response packet destined for the terminal

from the external network and transmitting it the response to the mobile telephone; and

upon receiving the response packet from the mobile telephone, the terminal verifying

an operation of the network application based on the response packet and preparing statistic

data for the received packet.

12. (Currently Amended) The verification method as claimed in claim 11, further

comprising:

assigning an internet Internet protocol address individually to the terminal, the packet

service simulator and the mobile telephone; and

the packet service simulator broadcasting an address resolution protocol (ARP)

packet, including an internet Internet protocol address of the terminal and a physical address

of the simulator, to the external network and recording it on a gateway for connection to the

external network so as to receive a packet having the address of the terminal;

13. (Currently Amended) The verification method as claimed in claim 11, wherein the

step of the terminal transmitting the internet Internet protocol packet to the mobile telephone

comprises:

establishing point-to-point protocol (PPP) access to the mobile telephone; and

DCDB01 20784724.1

transmitting the <u>internet</u> <u>Internet</u> protocol packet to the mobile telephone according to a PPP protocol.

14. (Currently Amended) The verification system as claimed in claim 11, wherein the step of the packet service simulator receiving the response packet destined for the terminal from the external network comprises:

transmitting to the external network the ARP response packet having a physical address of the simulator and an <u>internet Internet</u> protocol address of the terminal to the ARP request packet requesting the physical address of the terminal sent from the external network; and

receiving the response packet destined for the terminal.

15. (Original) The verification method as claimed in claim 11, further comprising:
the terminal requesting cancellation of a packet call established between the mobile telephone and the packet service simulator;

the mobile telephone transmitting a call cancellation control message corresponding to the cancellation request to the packet service simulator; and

the packet service simulator canceling the packet call to the mobile telephone based on the received control message and transmitting a corresponding response message to the mobile telephone to inform that the packet call is cancelled.

16. (Original) The verification method as claimed in claim 11, wherein the mobile telephone is linked to the packet service simulator via a local area network (LAN) and to the terminal via a universal serial bus (USB).